



**WAGO 4-CONDUCTOR GROUND TERMINAL BLOCK; 2.5 MM<sup>2</sup>; SUITABLE FOR EX E  
II APPLICATIONS; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE  
CLAMP®; 2,50 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Latime: 5 mm / 0.197 inch;  
Inaltime from upper-edge of DIN-rail: 28 mm / 1.102 inch;  
Adancime: 75 mm / 2.953 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,132; MJ  
Greutate: 12,8; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454100919;

Customs tariff number: 85369010000;  
Pret: 31,65 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-ground-terminal-block-2-5-mm2-suitable-for-ex-e-ii-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-2-50-mm2-green-yellow-150659>