



**WAGO TERMINAL BLOCK FOR PLUGGABLE MODULES; 14-POLE; WITH 4-  
CONDUCTOR TERMINAL BLOCKS; WITH ORANGE SEPARATOR; FOR DIN-RAIL 35  
X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; GRAY**

Rated continuous current: 10; A  
Tensiune nominala: 400; V  
Tensiune nominala de supratensiune: 6; kV  
Pollution degree: 3;  
Total number of potentials: 2;  
Numar tipuri de conexiuni: 4;  
Tehnologie conexiune: CAGE CLAMP®;  
Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 14 AWG;  
Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 14 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Wiring type: Front-entry wiring;  
Latime: 37 mm / 1.457 inch;  
Inaltime from upper-edge of DIN-rail: 28 mm / 1.102 inch;  
Adancime: 73 mm / 2.874 inch;  
Tip montaj: DIN-35 rail;  
Culoare: gray;  
Fire load: 1,042; MJ  
Greutate: 60; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918636414;  
Customs tariff number: 85369010000;  
Pret: 106,84 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/terminal-block-for-pluggable-modules-14-pole-with-4->

conductor-terminal-blocks-with-orange-separator-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm<sup>2</sup>-cage-clamp-2-50-mm<sup>2</sup>-gray-150709