



**WAGO 2-CONDUCTOR TERMINAL BLOCK; SUITABLE FOR EX I APPLICATIONS;
WITHOUT PUSH-BUTTONS; WITH SNAP-IN MOUNTING FOOT; FOR PLATE
THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 MM Ø; 2.5 MM²; CAGE CLAMP®; 2,50
MM²; BLUE**

Tesiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime de la fata: 27.6 mm / 1.087 inch;

Adancime: 33.4 mm / 1.315 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: blue;

Fire load: 0,073; MJ

Greutate: 4,1; g

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918480031;
Customs tariff number: 85369010000;
Pret: 5,37 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-terminal-block-suitable-for-ex-i-applications-without-push-buttons-with-snap-in-mounting-foot-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-blue-150724>