



Image coming soon

**WAGO 2-CONDUCTOR TERMINAL BLOCK; ON BOTH SIDES WITH PUSH-BUTTON;
WITH FIXING FLANGE; FOR SCREW OR SIMILAR MOUNTING TYPES; FIXING
HOLE 3.2 MM Ø; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; LIGHT GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool; Push-button;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 1;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 6 mm / 0.236 inch;

Inaltime de la fata: 23.2 mm / 0.913 inch;

Adancime: 28 mm / 1.102 inch;

Design: horizontal;

Tip montaj: Mounting flange;

Marking level: Side marking;

Culoare: light gray;

Fire load: 0,052; MJ

Greutate: 2,5; g

Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4044918619264;
Customs tariff number: 85369010000;
Pret: 2,87 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-terminal-block-on-both-sides-with-push-button-with-fixing-flange-for-screw-or-similar-mounting-types-fixing-hole-3-2-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-light-gray-150759>