



**WAGO TRIPLE-DECK TERMINAL BLOCK; THROUGH/THROUGH/THROUGH  
TERMINAL BLOCK; L/L/L; SUITABLE FOR EX E II APPLICATIONS; FOR DIN-RAIL  
35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; LIGHT GRAY**

Ratings per: IEC/EN 60947-7-1;

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala EN (Ex e II): 420; V

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 6;

Total number of potentials: 3;

Numar nivele: 3;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 52.5 mm / 2.067 inch;

Adancime: 106 mm / 4.173 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Potential marking: L/L/L;

Marking level: Side marking;

Culoare: light gray;

Fire load: 0,278; MJ

Greutate: 17,5; g

Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4045454129729;  
Customs tariff number: 85369010000;  
Pret: 18,93 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/triple-deck-terminal-block-through-through-through-terminal-block-1-1-1-suitable-for-ex-e-ii-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-light-gray-150835>