



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-ENDED; 5-POLE;
COD. I; H05Z1Z1-F 5G 1.5 MM²; 3 M; 1,50 MM²; BLUE

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition
plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 12; A

Strip length: 9 mm / 0.35 inch;

Numar poli: 5;

Total number of potentials: 5;

Ground function: with preceding ground contact;

Conductor preparation: tip-bonded;

Sheathed cable diameter: 9,3 ... 11,6 mm;

Sectiunea transversala a firului: 1,5; mm²

Strip length (outer insulation): 45; mm

Connection type: Plug - Free end;

Distanta intre pini: 4,4 mm / 0.173 inch;

Total length: 3; m

Technologie: DALI;

Coding: I;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: when locked: > 80N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: ?200, without resistive load 100, with resistive load IN = 16 A, tested

(1.5mm²/AWG 16);
Connection type: Plug - free end;
Type of pre-assembled cable: Connecting cable;
Cable type: H05Z1Z1-F 5G1.5;
Marking: N ? L - +;
Protection type: IP20;
Note on protection type: IP40 when mated;
Potential marking: N ? L - +;
Application: Lighting management;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Fire load: 6,89; MJ
Connector Culoare: blue;
Printing color of mating face: white;
Strain relief Culoare: black;
Printing color of strain relief: white;
Sheathed cable Culoare: black;
Printing color of sheathed cable: white;
Halogen-free: Yes;
Greutate: 448,4; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: PL;
GTIN: 4055143399494;
Customs tariff number: 85444290900;
Pret: 100,51 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-5-pole-cod-i-h05z1z1-f-5g-1-5-mm2-3-m-1-50-mm2-blue-150853>