



WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; WITH LEVER AND PUSH-BUTTON; 6 MM²; WITH TEST PORT; SUITABLE FOR EX I APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 6,00 MM²; BLUE

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 41; A

Curent nominal 2: 55; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Lever; Push-button;

Tip actionare 2: Push-in; Push-button; Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 1 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 10 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar total de conexiuni: 3;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;
Latime: 7,5 mm / 0.295 inch;
Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;
Adancime: 90,8 mm / 3.575 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Greutate: 17,5; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143742498;
Customs tariff number: 85369010000;
Pret: 18,51 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-through-terminal-block-with-lever-and-push-button-6-mm2-with-test-port-suitable-for-ex-i-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-6-00-mm2-blue-150904>