



**WAGO 1-CONDUCTOR POWER DISTRIBUTION DISCONNECT TERMINAL BLOCK;  
35 MM<sup>2</sup>; WITH INTEGRATED END PLATE; CAGE CLAMP®; 35,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 125; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Solid conductor: 6 ... 35 mm<sup>2</sup> / 8 ... 2 AWG;

Strip length: 23 mm / 0.91 inch;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 16 mm / 0.63 inch;

Inaltime from upper-edge of DIN-rail: 44,5 mm / 1.752 inch;

Adancime: 116,5 mm / 4.587 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: gray;

Greutate: 91,5; g

Product Group: 17 (TOP JOB installation terminal blocks);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454601898;

Customs tariff number: 85365080900;

Pret: 73,09 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-power-distribution-disconnect-terminal-block-35-mm2-with-integrated-end-plate-cage-clamp-35-00-mm2-gray-150981>