



WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; WITH PUSH-BUTTON; 4 MM²; WITH TEST PORT; SUITABLE FOR EX I APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 4,00 MM²; BLUE

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 32; A

Curent nominal 2: 41; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 30; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 30; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Push-button;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm²;

Solid conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Solid conductor; push-in termination: 1 ... 6 mm² / 14 ... 10 AWG;

Fine-stranded conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Fine-stranded conductor; with insulated ferrule: 1,5 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1,5 ... 4 mm² / 18 ... 12 AWG;

Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;

Numar total de conexiuni: 3;

Total number of potentials: 1;

Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 6,2 mm / 0.244 inch;
Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;
Adancime: 65,5 mm / 2.579 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Greutate: 9,2; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143711418;
Customs tariff number: 85369010000;
Pret: 7,94 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-through-terminal-block-with-push-button-4-mm2-with-test-port-suitable-for-ex-i-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-4-00-mm2-blue-151429>