



**WAGO FEEDTHROUGH TERMINAL BLOCK; CONDUCTOR/SOLDER/CRIMP QUICK
DISCONNECT TERMINAL; PLATE THICKNESS: 1.5 MM; 4 MM²; PIN SPACING 6 MM;
1-POLE; CAGE CLAMP®; 4,00 MM²; GRAY**

Ratings per: IEC/EN 60664-1;

Ratings (note): Solder connection;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 20; A

Ratings per: IEC/EN 60664-1;

Ratings (note) 2: Quick connect contact;

Tensiune nominala (III/3) 2: 320; V

Tensiune nominala de supratensiune (III/3) 2: 4; kV

Tensiune nominala (III/2) 2: 320; V

Tensiune nominala de supratensiune (III/2) 2: 4; kV

Tensiune nominala (II/2) 2: 630; V

Tensiune nominala de supratensiune (II/2) 2: 4; kV

Curent nominal 2: 6; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 6; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 6; A

Tensiune nominala UL (Use Group D): 600; V

Curent nominal UL (Use Group D): 5; A

Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 6; A
Tensiune nominala CSA (Use Group C): 300; V
Curent nominal CSA (Use Group C): 6; A
Tensiune nominala CSA (Use Group D): 600; V
Curent nominal CSA (Use Group D): 5; A
Tehnologie conexiune: CAGE CLAMP®;
Number of connection points (connection type): 1;
Tip actionare: Operating tool;
Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 ... 2,5 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²;
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;
Numar poli: 1;
Tehnologie conexiune 2: Solder connection;
Number of connection points: 1;
Tehnologie conexiune 3: Quick connect contact;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Numar tipuri de conexiuni: 2;
Numar nivele: 1;
Distanta intre pini: 6 mm / 0.236 inch;
Latime: 6 mm / 0.236 inch;
Inaltime: 38,5 mm / 1.516 inch;
Inaltime de la fata: 22 mm / 0.866 inch;
Adancime: 26 mm / 1.024 inch;
Housing sheet thickness: 1,5 ... 1,5 mm / 0.059 ... 0.059 inch;
Tip montaj: Snap-in mounting foot;
Tip montaj: Feed-through mounting;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,054; MJ
Greutate: 3,6; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4044918794374;
Customs tariff number: 85369010000;
Pret: 13,14 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/feedthrough-terminal-block-conductor-solder-crimp-quick-disconnect-terminal-plate-thickness-1-5-mm-4-mm2-pin-spacing-6-mm-1-pole-cage-clamp-4-00-mm2-gray-151600>