



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 10 MM<sup>2</sup>; SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 10,00 MM<sup>2</sup>; YELLOW**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 57; A

Curent nominal 2: 76; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 65; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 65; A

Certificari: UL 1059;

Tensiune nominala EN (Ex e II): 550; V

Curent nominal (Ex e II): 51; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 10 mm<sup>2</sup>;

Solid conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;

Solid conductor; push-in termination: 4 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;

Fine-stranded conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;

Fine-stranded conductor; with insulated ferrule: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;

Strip length: 17 ... 19 mm / 0.67 ... 0.75 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Number of jumper slots: 2;  
Latime: 10 mm / 0.394 inch;  
Inaltime from upper-edge of DIN-rail: 36,9 mm / 1.453 inch;  
Adancime: 67,8 mm / 2.669 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: yellow;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 18,2; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143645911;  
Customs tariff number: 85369010000;  
Pret: 13,38 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-10-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-10-00-mm2-yellow-151652>