



**WAGO STACKABLE 2-CONDUCTOR PCB TERMINAL BLOCK; WITH FUSE  
MOUNTING; 2.5 MM<sup>2</sup>; PIN SPACING 5.08 MM; 1-POLE; CAGE CLAMP®; 2,50 MM<sup>2</sup>;  
ORANGE**

Ratings per: IEC/EN 60664-1;

Ratings (note): Individual arrangement;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 15; A

Nominal current (individual arrangement): 15; A

Nominal current (block arrangement): 10; A

Ratings per: IEC/EN 60664-1;

Ratings (note) 2: Block arrangement;

Tensiune nominala (III/3) 2: 320; V

Tensiune nominala de supratensiune (III/3) 2: 4; kV

Tensiune nominala (III/2) 2: 320; V

Tensiune nominala de supratensiune (III/2) 2: 4; kV

Tensiune nominala (II/2) 2: 630; V

Tensiune nominala de supratensiune (II/2) 2: 4; kV

Curent nominal 2: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;  
Tensiune nominala CSA (Use Group B): 300; V  
Curent nominal CSA (Use Group B): 10; A  
Tensiune nominala CSA (Use Group D): 300; V  
Curent nominal CSA (Use Group D): 10; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,25 ... 1,5 mm<sup>2</sup>;  
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1,5 mm<sup>2</sup>;  
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;  
Conductor connection direction to PCB: 90; °  
Numar poli: 1;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Distanta intre pini: 5,08 mm / 0.2 inch;  
Latime: 7,1 mm / 0.28 inch;  
Inaltime: 27,2 mm / 1.071 inch;  
Inaltime de la fata: 23,2 mm / 0.913 inch;  
Adancime: 43,5 mm / 1.713 inch;  
Lungimea pinului de contact: 4; mm  
Solder pin dimensions: 1 x 0,8 mm;  
Diametrul de gaurire cu toleranta: 1,4 (+0,1) mm;  
PCB contact: THT;  
Solder pin arrangement: within the terminal block (in-line);  
Number of solder pins per potential: 2;  
Culoare: orange;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ESu);  
Contact plating: tin-plated;  
Fire load: 0,088; MJ  
Greutate: 5,4; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4045454265199;  
Customs tariff number: 85369095990;  
Pret: 9,91 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/stackable-2-conductor-pcb-terminal-block-with-fuse-mounting-2-5-mm2-pin-spacing-5-08-mm-1-pole-cage-clamp-2-50-mm2-orange-151691>