



**WAGO 2-CONDUCTOR TERMINAL STRIP; SUITABLE FOR EX E II APPLICATIONS;
9-POLE; WITHOUT PUSH-BUTTONS; WITH FIXING FLANGES; FOR SCREW OR
SIMILAR MOUNTING TYPES; FIXING HOLE 3.2 MM Ø; 2.5 MM²; CAGE CLAMP®;
2,50 MM²; LIGHT GRAY**

Tensiune nominala EN (Ex e II): 690; V
Curent nominal (Ex e II): 23; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 9;
Numar total de conexiuni: 18;
Total number of potentials: 9;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): 12 AWG: THHN, THWN;
Latime: 70 mm / 2.756 inch;
Inaltime de la fata: 22,1 mm / 0.87 inch;
Adancime: 32 mm / 1.26 inch;
Module Latime: 6 mm / 0.236 inch;
Design: horizontal type;
Marking level: Center marking;
Culoare: light gray;
Fire load: 0,719; MJ
Greutate: 36; g

Product Group: 9 (Std. Chassis Mt. Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918423120;
Customs tariff number: 85369010000;
Pret: 43,71 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-terminal-strip-suitable-for-ex-e-ii-applications-9-pole-without-push-buttons-with-fixing-flanges-for-screw-or-similar-mounting-types-fixing-hole-3-2-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-light-gray-151708>