



WAGO 2-CONDUCTOR/1-PIN CARRIER TERMINAL BLOCK; SUITABLE FOR EX NA APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;

Current nominal: 20; A

Nominal voltage EN (Ex e II): 630; V

Connection technology: Push-in CAGE CLAMP®;

Number of connection points (connection type): 2;

Tip action: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Number of connection points: 1;

Total number of connections: 2;

Total number of potentials: 1;

Number of levels: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Width: 5,2 mm / 0.205 inch;

Height from upper edge of DIN-rail: 32,5 mm / 1.28 inch;

Depth: 59,2 mm / 2.331 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,136; MJ
Greutate: 6,3; g
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4055143329422;
Customs tariff number: 85366990990;
Pret: 9,44 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-1-pin-carrier-terminal-block-suitable-for-ex-na-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-151728>