



**WAGO 1-CONDUCTOR POWER DISTRIBUTION DISCONNECT TERMINAL BLOCK;
10 MM²; CAGE CLAMP®; 10,00 MM²; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 57; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 10 mm² / 24 ... 8 AWG;

Fine-stranded conductor: 0,2 ... 10 mm² / 24 ... 8 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Solid conductor 2: 0,2 ... 16 mm² / 24 ... 6 AWG;

Fine-stranded conductor 2: 0,2 ... 16 mm² / 24 ... 6 AWG;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 10 mm / 0.394 inch;

Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;

Adancime: 82,5 mm / 3.248 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Greutate: 32,9; g

Product Group: 17 (TOP JOB installation terminal blocks);

Tip ambalare: BOX;

Tara de origine: PL;
GTIN: 4045454016999;
Customs tariff number: 85365080900;
Pret: 21,20 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-power-distribution-disconnect-terminal-block-10-mm2-cage-clamp-10-00-mm2-gray-152027>