



**WAGO FEMALE CONNECTOR; WITH DIRECT GROUND CONTACT; 4-POLE; 1,00
MM²; WHITE**

Tensiune nominala (III/2): 500; V
Tensiune nominala de supratensiune (III/2): 4; kV
Curent nominal: 6; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Strip length: 8 mm / 0.31 inch;
Numar poli: 4;
Numar tipuri de conexiuni: 1;
Latime: 32 mm / 1.26 inch;
Inaltime de la fata: 34 mm / 1.339 inch;
Adancime: 32 mm / 1.26 inch;
Culoare: white;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,141; MJ
Greutate: 7,7; g
Temperature stability: 105; °C
Product Group: 8 (Misc. Chassis Mount Blocks);
Tip ambalare: bag;
Tara de origine: PL;
GTIN: 4044918499552;
Customs tariff number: 85369010000;

Pret: 19,47 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/female-connector-with-direct-ground-contact-4-pole-1-00-mm2-white-152031>