



**WAGO DOUBLE-DECK TERMINAL BLOCK; 4-CONDUCTOR THROUGH TERMINAL BLOCK; WITH END PLATE; L; WITH MARKER CARRIER; INTERNAL COMMONING; CONDUCTOR ENTRY WITH VIOLET MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 1 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 1,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 13,5; A

Curent nominal 2: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 15; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1 mm<sup>2</sup>;

Solid conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;

Solid conductor; push-in termination: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 16 AWG;

Fine-stranded conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 2;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Latime: 4,2 mm / 0.165 inch;  
Inaltime from upper-edge of DIN-rail: 61,8 mm / 2.433 inch;  
Adancime: 69,7 mm / 2.744 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Potential marking: L;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,229; MJ  
Greutate: 10,1; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821037705;  
Customs tariff number: 85369010000;  
Pret: 18,09 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/double-deck-terminal-block-4-conductor-through-terminal-block-with-end-plate-l-with-marker-carrier-internal-commoning-conductor-entry-with-violet-marking-for-din-rail-35-x-15-and-35-x-7-5-1-mm2-push-in-cage-clamp-1-00-mm2-gray-152196>