



WAGO POWER SUPPLY CONNECTOR

Tensiune nominala (III/2): 400; V

Tensiune nominala de supratensiune (III/2): 4; kV

Curent nominal: 18; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Tehnologie conexiune: PUSH WIRE®;

Solid conductor: 0,5 ... 1,5 mm² / 20 ... 16 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 3;

Solid conductor 2: 0,5 ... 2,5 mm² / 20 ... 14 AWG;

Numar total de conexiuni: 12;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Latime: 28,5 mm / 1.122 inch;

Inaltime: 19 mm / 0.748 inch;

Adancime: 24,5 mm / 0.965 inch;

Fire load: 0,145; MJ

Greutate: 8,8; g

Product Group: 8 (Misc. Chassis Mount Blocks);

Tip ambalare: bag;

Tara de origine: PL;

GTIN: 4044918397155;

Customs tariff number: 85369010000;

Pret: 8,42 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/power-supply-connector-152211>