



**WAGO 2-CONDUCTOR MODULAR PCB CONNECTOR; FOR SOLDER PIN STRIP;
PUSH-BUTTON; 0.8 MM Ø; PIN SPACING 3.5 MM; 10-POLE; 0,50 MM²; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 2; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 2; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 2; A

Certificari: UL 1059;

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Push-button;

Solid conductor: 0,14 ... 0,5 mm² / 26 ... 20 AWG;

Conductor diameter: 0,4 ... 0,8 mm;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Conductor connection direction to PCB: 0; °

Numar poli: 10;

Numar total de conexiuni: 20;

Total number of potentials: 10;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 3,5 mm / 0.138 inch;

Latime: 35 mm / 1.378 inch;
Inaltime: 13,1 mm / 0.516 inch;
Adancime: 10,5 mm / 0.413 inch;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for PCB;
Mating direction to the PCB: 90; °
PCB contact: THT;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Copper alloy;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,13; MJ
Greutate: 5; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454040215;
Customs tariff number: 85369010000;
Pret: 12,84 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-modular-pcb-connector-for-solder-pin-strip-push-button-0-8-mm-oe-pin-spacing-3-5-mm-10-pole-0-50-mm2-gray-152261>