



**PALAZZOLI RINO STAINLESS STEEL-GLASS LIGHTING FIXTURE 2X49W WITH
WHITE REFLECTOR AND ELECTRONIC POWER SUPPLY 230V 50HZ G5 T5**

Puterea l?mpii: 2x49W
Tipul l?mpii: G5
Tip surs? de lumin?: T5
Dimensiuni: 1600x200x100 mm
Indexul UGR:
Tipul gaurei: M20
Tipul de tratament: finisaje naturale
Temperatura camerei de depozitare min: -40 ° C
Temperatura camerei de depozitare max: + 70 ° C
Optica: simetric?
Rezisten?a la ?oc: IK09 al doilea IEC / EN 62262
Sec?iunea de conductor Max: 2,5 mm²
Clasa de coroziune: C4 (ISO 9223)
Diametru de strangere: min 7 mm; Max 14 mm.
Frecven??: 0/50 / 60Hz
Tipul optica: reflector alb RAL9016
Gradul de protec?ie: IP66 / IP67
Tip difuzor: sticl? transparent? temperat?
Unitate de alimentare: electronic?
Min. Amb. Temp.: -25 ° C
Max. Amb. Temp.: + 50 ° C
Tensiune de operare evaluat?: 220V-240V
Material de fabrica?ie: o?el inoxidabil AISI 304
Sistem de montare: fixare pe fund
Sistem de control / Dimming: Standard On-off
Pret: 1.800,50 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/rino-stainless-steel-glass-lighting-fixture-2x49w-with-white-reflector-and-electronic-power-supply-230v-50hz-g5-t5-190375>