



**PALAZZOLI RINO PAINTED STEEL-POLYCARBONATE LIGHTING FIXTURE**  
**(1+1)X36W WITH SYMMETRICAL REFLECTOR IN ALUMINIUM FOR EMERGENCY**  
**230V 50HZ G13T8**

Puterea l?mpii: (1 + 1) x36W

Tipul l?mpii: G13

Tip surs? de lumin?: T8

Dimensiuni: 1300x200x100 mm

Flux de urgen??: 0,12

Indexul UGR:

Tipul gaurei: M20

Tipul de tratament: Zincliplate

Temperatura camerei de depozitare min: -40 ° C

Temperatura camerei de depozitare max: + 70 ° C

Optica: simetric?

Rezisten?a la ?oc: IK09 al doilea IEC / EN 62262

Sec?iunea de conductor Max: 2,5 mmqq

Clasa de coroziune: C3 (ISO 9223)

Culoare: Alb Ral 9016

Diametru de strangere: min 7 mm; Max 14 mm.

Frecven??: 0/50 / 60Hz

Tipul opticelor: reflector de aluminiu ultra luminos

Gradul de protec?ie: IP66

Difuzor Tip: Policarbonat stabilizat UV stabilizat

Unitate de alimentare: electronic?

Min. Amb. Temp.: -25 ° C

Max. Amb. Temp.: + 50 ° C

Tensiune de operare evaluat?: 220V-240V

Material de fabrica?ie: o?el zinclat ?i vopsit

Sistem de montare: fixare pe fund

Finisarea suprafeței: cuptor de vopsea poliester atoxic, anti-UV Polimerizat

Sistem de control / Dimming: Standard On-off

Pret: 2.133,71 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/rino-painted-steel-polycarbonate-lighting-fixture-1-1-x36w-with-symmetrical-reflector-in-aluminium-for-emergency-230v-50hz-g13t8-190435>