



**PALAZZOLI RINO PAINTED STEEL-POLYCARBONATE LIGHTING FIXTURE 2X24W  
WITH SYMMETRICAL REFLECTOR IN ALUMINIUM AND ELECTRONIC POWER  
SUPPLY 200-250V 50HZ G5 T5**

Puterea l?mpii: 2x24W  
Tipul l?mpii: G5  
Tip surs? de lumin?: T5  
Dimensiuni: 690x200x100 mm  
Indexul UGR:  
Tipul gaurei: M20  
Tipul de tratament: Zincliplate  
Temperatura camerei de depozitare min: -40 ° C  
Temperatura camerei de depozitare max: + 70 ° C  
Optica: simetric?  
Rezisten?a la ?oc: IK09 al doilea IEC / EN 62262  
Sec?iunea de conductor Max: 2,5 mmq  
Clasa de coroziune: C3 (ISO 9223)  
Culoare: Alb Ral 9016  
Diametru de strangere: min 7 mm; Max 14 mm.  
Frecven??: 50 / 60Hz  
Tipul opticelor: reflector de aluminiu ultra luminos  
Gradul de protec?ie: IP66  
Difuzor Tip: Policarbonat stabilizat UV stabilizat  
Unitate de alimentare: electronic?  
Min. Amb. Temp.: -25 ° C  
Max. Amb. Temp.: + 50 ° C  
Tensiune de operare evaluat?: 220V-240V  
Material de fabrica?ie: o?el zinclat ?i vopsit  
Sistem de montare: fixare pe fund

Finisarea suprafeței: cuptor de vopsea poliester atoxic, anti-UV Polimerizat

Sistem de control / Dimming: Standard On-off

Pret: 1.268,41 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/rino-painted-steel-polycarbonate-lighting-fixture-2x24w-with-symmetrical-reflector-in-aluminium-and-electronic-power-supply-200-250v-50hz-g5-t5-190436>