



**GEWISS SMOOTH WALLS ENCLOSURE - WITH TERMINAL BLOCKS N (2X16)+(7X10)
E (2X16)+(7X10) - 8M IP65**

Clas? izola?ie - II (conform standardelor IEC 61140)

Culoare - Gri RAL 7035

Dim. exterioare LxHxP (mm) - 215x210x100

Clas? de protec?ie IP - IP65

Putere disipabil? (W) - 16

Cod IK - IK09

Tensiune nominal? - 400 V

Culoare u?? - Transparent fumuriu

Cutii cu borne - 80 A - orificii cu ?uruburi IP20

Nr. module EN 50022 - 8

Curent nominal - 125 A

Glow Test conductori - 650 °C

Temperatur? de operare - -25 +60 °C

Tip de material - F?r? halogen conform EN 60754-2

Electrocod - 0321

Termo-presiune cu bil? - 70 °C

Accesorii pentru restabilirea izola?iei - Capete de ?uruburi (GW44623) sau console de fixare in r??in? (GW44621)

Standard - EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49

Tensiune izola?ie - 1000 V conform EN 62208 atat in AC, cat ?i in DC

Stalp 1 (mm²) - N/E (2x16) + (7x10)

Stalp 2 (mm²) - N/E (2x16) + (7x10)

Ware number - 85381000

Pret: 99,91 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/smooth-walls-enclosure-with-terminal-blocks-n-2x16-7x10->

e-2x16-7x10-8m-ip65-209304