



**GEWISS TABLOU ELECTRIC WITH PANELS WITH WINDOW AND EXTRACTABLE  
FRAME - WITH TERMINAL BLOCK N 2 X [(3X16)+(17X10)] E 2 X [(3X16)+(17X10)] -  
(18X4) 72M IP65**

Clas? izola?ie - II (conform standardelor IEC 61140)

Culoare - Gri RAL 7035

Dim. exterioare LxHxP (mm) - 410x878x160

Clas? de protec?ie IP - IP65

Putere disipabil? (W) - 89

Cod IK - IK09

Tensiune nominal? - 400 V

Culoare u?? - Transparent fumuriu

Cutii cu borne - 80 A - orificii cu ?uruburi IP20

Nr. module EN 50022 - 72 (18x4)

Curent nominal - 125 A

Glow Test conductori - 650 °C

Temperatur? de operare - -25 +60 °C

Tip de material - F?r? halogen conform EN 60754-2

Electrocod - 0321

Termo-presiune cu bil? - 70 °C

Accesorii pentru restabilirea izola?iei - Capete de ?uruburi (GW44623) sau console de fixare in r??in? (GW44621)

Standard - EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49

Tensiune izola?ie - 1000 V conform EN 62208 atat in AC, cat ?i in DC

Stalp 1 (mm<sup>2</sup>) - N/E 2x[(3x16) + (17x10)]

Stalp 2 (mm<sup>2</sup>) - N/E 2x[(3x16) + (17x10)]

Ware number - 85371098

Pret: 1.029,48 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tablou-electric-with-panels-with-window-and-extractable-frame-with-terminal-block-n-2-x-3x16-17x10-e-2-x-3x16-17x10-18x4-72m-ip65-209315>