



**GEWISS FLUSH-MOUNTING ENCLOSURE WITH SMOKED TRANSPARENT DOOR
WITH EXTRACTABLE FRAME - WITH TERMINAL BLOCK N (2X16)+(7X10) E
(2X16)+(7X10) - 8 MODULE IP40**

Clas? izola?ie - II (conform standardelor IEC 61140)
Culoare - Alb RAL 9016
Dim. exterioare LxHxP (mm) - 240x195x85
Clas? de protec?ie IP - IP40
Instalare - Cu montaj ingropat
Putere disipabil? (W) - 20
Cod IK - IK08
Tensiune nominal? - 400 V
Culoare u?? - Transparent fumuriu
Cutii cu borne - 80 A - orificii cu ?uruburi IP20
Nr. module EN 50022 - 8
Curent nominal - 125 A
Glow Test conductori - 650 °C
Temperatur? de operare - -15 +60 °C
Tip de material - F?r? halogen conform EN 60754-2
Electrocod - 0311
Termo-presiune cu bil? - 70 °C
Standard - EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49
Tensiune izola?ie - 750 V
Stalp 1 (mm²) - N/E (2x16) + (7x10)
Stalp 2 (mm²) - N/E (2x16) + (7x10)
Ware number - 85381000
Pret: 49,51 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/flush-mounting-enclosure-with-smoked-transparent-door->

with-extractable-frame-with-terminal-block-n-2x16-7x10-e-2x16-7x10-8-module-ip40-209431