



**GEWISS FLUSH-MOUNTING ENCLOSURE WITH SMOKED TRANSPARENT DOOR  
WITH EXTRACTABLE FRAME - WITH TERMINAL BLOCK N (3X16)+(11X10) E  
(3X16)+(11X10) - 8 MODULE IP40**

Clas? izola?ie - II (conform standardelor IEC 61140)  
Culoare - Alb RAL 9016  
Dim. exterioare LxHxP (mm) - 330x270x85  
Clas? de protec?ie IP - IP40  
Instalare - Cu montaj ingropat  
Putere disipabil? (W) - 36  
Cod IK - IK08  
Tensiune nominal? - 400 V  
Culoare u?? - Transparent fumuriu  
Cutii cu borne - 80 A - orificii cu ?uruburi IP20  
Nr. module EN 50022 - 12  
Curent nominal - 125 A  
Glow Test conductori - 650 °C  
Temperatur? de operare - -15 +60 °C  
Tip de material - F?r? halogen conform EN 60754-2  
Electrocod - 0311  
Termo-presiune cu bil? - 70 °C  
Standard - EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49  
Tensiune izola?ie - 750 V  
Stalp 1 (mm<sup>2</sup>) - N/E (3x16) + (11x10)  
Stalp 2 (mm<sup>2</sup>) - N/E (3x16) + (11x10)  
Ware number - 85381000  
Pret: 62,52 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/flush-mounting-enclosure-with-smoked-transparent-door->

