



**GEWISS WATERTIGHT ENCLOSURE FOR EMERGENCY SYSTEM WITH
ILLUMINATED INTERRUPTOR CU REVENIRE FOR LOCALISATION AND TWO
CONTACTS**

Curent nominal (A) - 125
Clas? izola?ie - II
Culoare - RAL 3000 Ro?u
Dim. exterioare LxHxP (mm) - 120x120x50
Clas? de protec?ie IP - IP55
Instalare - Perete
Material - Tehnopolimer
Cod IK - IK08
Tensiune nominal? (V) - 400
Dot?ri - Buton cu revenire + 2 contacte
Glow Test conductori - 650 °C
Temperatur? de operare - -25 +60 °C
Tip de material - F?r? halogen conform EN 60754-2
Electrocod - 0321
Nr. de contacte care pot fi instalate - 4
Termo-presiune cu bil? - 70 °C
Standard - EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49
Tensiune izola?ie - 750 V
Ware number - 85371098
Pret: 227,59 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/watertight-enclosure-for-emergency-system-with-illuminated-interruptor-cu-revenire-for-localisation-and-two-contacts-209503>