



**GEWISS Q-DIN 14 ACS - MOBILE-PORTABLE - WITH CARRIAGE - 2 2P+E 16A IEC309  
+ 2 3P+E 16A IEC 309 + 2 PRIZA SCHUKO 16A - IP44**

Tip - Q-DIN 14 ACS

tip plac? - Cablat

Dim. exterioare LxHxP (mm) - 320x510x120

Greutate (Kg) - 22

Conformitate cu standardele - EN 61439-4 (ASC)

Caracteristici - Rezisten?? UV (EN 62208)

Clas? de protec?ie IP - IP44

Cod IK - IK09

Glow test conductori - 650 °C

Termo-presiune cu bil? - 70 °C

Clas? izola?ie - II

Surs? de alimentare - Fi?? mobil? 2P+E 16 A

Nr. poli - 3P+N+T

Putere prevazut?/alimentare - 17

Intrerup?tor general - RCBO 32A 4P 6 kA 0,03 A - tip c.a.

Protec?ie circuite - MCB

Nr. prize - 6

Priz? 2P+T 16A - IEC 309 - 2

Priz? 3P+T 16A - IEC 309 - 2

priz? standard german 16 A - 2

Lungime cablu - 25 m

Dot?ri - C?rucior cu dou? ro?i ?i tambur

Electrocod - 139

Ware number - 85371098

Pret: 7.514,91 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/q-din-14-ac-s-mobile-portable-with-carriage-2-2p-e-16a-iec309-2-3p-e-16a-iec-309-2-priza-schuko-16a-ip44-211795>