



**GEWISS Q-DIN 20 ACS - MOBILE-PORTABLE - WITH CARRIAGE - 2 2P+E 16A IB + 1
3P+E 16A IB + 1 3P+E 32A IB - IP65**

Tip - Q-DIN 20 ACS

tip plac? - Cablat

Dim. exterioare LxHxP (mm) - 450x560x120

Greutate (Kg) - 31

Conformitate cu standardele - EN 61439-4 (ASC)

Caracteristici - Rezisten?? UV (EN 62208)

Clas? de protec?ie IP - IP65

Cod IK - IK09

Glow test conductori - 650 °C

Termo-presiune cu bil? - 70 °C

Clas? izola?ie - II

Surs? de alimentare - Fi?? mobil? 2P+E 16 A

Nr. poli - 3P+N+T

Putere prevazut?/alimentare - 33

MT MCB RCCB principal - RCD 40 A 4P 0,03 A - tip c.a.

Protec?ie circuite - MCB

Nr. prize - 4

Priz? 2P+T 16A - IB - 2

Priz? 3P+T 16A - IB - 1

Priz? 3P+T 32A - IB - 1

Lungime cablu - 35 m

Dot?ri - C?rucior cu dou? ro?i ?i tambur

Electrocod - 139

Ware number - 85371098

Pret: 8.904,91 LEI (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/q-din-20-ac-s-mobile-portable-with-carriage-2-2p-e-16a-ib-1-3p-e-16a-ib-1-3p-e-32a-ib-ip65-211797>