



GEWISS COMPACT SIGURANTA AUTOMATA - MTC 60 - 2P B CHARACTERISTIC 13A **- 1 MODUL**

Descriere - INTRERUP?TOR MAGNETOTERMIC COMPACT

Cod - MTC 60

Nr. poli - 2P

N. module - 1

Curent nominal - 13 A

Arc - B

Tensiune nominal? - 230 V

Standard - EN 60898, EN 60947-2

Frecven?? nominal? (Hz) - 50/60 Hz

Capacitate de intrerupere EN 60898 230V (Icn) - 6000 A

Capacitate de intrerupere EN 60898 (Ics) - 1 x Icn

Capacitate de intrerupere EN 60947-2 230V (Icu) - 10 kA

Capacitate de intrerupere EN 60947-2 (Ics) - 100% Icu

Tensiune de izolare - 500 V

Tensiune nominal? de rezisten?? la impulsuri - 4 kV

Tensiune minim? de operare - 12V ac/dc

Tensiune maxim? de operare - 440V AC / 220V DC

Rezisten?? electric? - 10000

Rezisten?? mecanic? - 20.000

Cablu cu sec?iune rigid? - $\leq 1 \times 16$ - $\leq 1 \times 10 + 1 \times 6$ mm²

Cablu cu sec?iune flexibil? - $\leq 1 \times 10$ - $\leq 2 \times 6$ mm²

Cuplu de strangere nominal - 1,2 Nm

Temperatur? de operare - -25 +60 °C

Temperatur? de stocare - -40 +70 °C

Electrocod - 1411

Ware number - 85362010

Pret: 95,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/compact-siguranta-automata-mtc-60-2p-b-characteristic-13a-1-modul-212609>