



GEWISS HIGH PERFORMANCE SIGURANTA AUTOMATA - MTHP 250 - 4P **CHARACTERISTIC C 25A - 6 MODULE**

Descriere - INTRERUP?TOR MAGNETOTERMIC CU PERFORMAN?E RIDICATE

Cod - MTHP 250

Nr. poli - 4P

N. module - 6

Curent nominal - 25 A

Arc - C

Tensiune nominal? - 230-400 V

Standard - EN 60898, EN 60947-2

Frecven?? nominal? (Hz) - 50/60 Hz

Capacitate de intrerupere EN 60898 230V (Icn) - 25000 A

Capacitate de intrerupere EN 60898 400V (Icn) - 25000 A

Capacitate de intrerupere EN 60898 (Ics) - 0.75 x Icn

Capacitate de intrerupere EN 60947-2 230V (Icu) - 30 kA

Capacitate de intrerupere EN 60947-2 400V (Icu) - 25 kA

Capacitate de intrerupere EN 60947-2 (Ics) - 75% Icu

Tensiune de izolare - 500 V

Tensiune nominal? de rezisten?? la impulsuri - 6 kV

Tensiune minim? de operare - 12V ac/dc

Tensiune maxim? de operare - 440V AC / 220V DC

Rezisten?? electric? - 10000

Rezisten?? mecanic? - 20.000

Cablu cu sec?iune rigid? - <=1x70 - <=2x25 - <=2x25+1x10 mm²

Cablu cu sec?iune flexibil? - <=1x50(2) - <=2x25 - <=3x16 mm²

Cuplu de strangere nominal - 3.5 / 3 (terminale)

Temperatur? de operare - -25 +60 °C

Temperatur? de stocare - -40 +70 °C

Electrocod - 1411

Ware number - 85362010

Pret: 1.385,70 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/high-performance-siguranta-automata-mthp-250-4p-characteristic-c-25a-6-module-213031>