



## **GEWISS HIGH PERFORMANCE SIGURANTA AUTOMATA - MTHP 160 - 2P** **CHARACTERISTIC D 63A- 3 MODULE**

Descriere - INTRERUP?TOR MAGNETOTERMIC CU PERFORMAN?E RIDICATE

Cod - MTHP 160

Nr. poli - 2P

N. module - 3

Curent nominal - 63 A

Arc - D

Tensiune nominal? - 230-400 V

Standard - EN 60898, EN 60947-2

Frecven?? nominal? (Hz) - 50/60 Hz

Capacitate de intrerupere EN 60898 230V (Icn) - 10000 A

Capacitate de intrerupere EN 60898 400V (Icn) - 10000 A

Capacitate de intrerupere EN 60898 (Ics) - 0.75 x Icn

Capacitate de intrerupere EN 60947-2 230V (Icu) - 20 kA

Capacitate de intrerupere EN 60947-2 400V (Icu) - 16 kA

Capacitate de intrerupere EN 60947-2 (Ics) - 50% Icu

Tensiune de izolare - 500 V

Tensiune nominal? de rezisten?? la impulsuri - 6 kV

Tensiune minim? de operare - 12V ac/dc

Tensiune maxim? de operare - 440V AC / 220V DC

Rezisten?? electric? - 10000

Rezisten?? mecanic? - 20.000

Cablu cu sec?iune rigid? - <=1x70 - <=2x25 - <=2x25+1x10 mm<sup>2</sup>

Cablu cu sec?iune flexibil? - <=1x50(2) - <=2x25 - <=3x16 mm<sup>2</sup>

Cuplu de strangere nominal - 3.5 / 3 (terminale)

Temperatur? de operare - -25 +60 °C

Temperatur? de stocare - -40 +70 °C

Electrocod - 1411

Ware number - 85362010

Pret: 799,27 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/high-performance-siguranta-automata-mthp-160-2p-characteristic-d-63a-3-module-213053>