



**GEWISS LAMPA PROIECTOR TIP ELIA FL - DALI - M2 - 60° OPTIC - CRI 80 4000 K -
IP66 - CLASS I - BLACK**

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Industry, Logistic, Facade, Sport

Optic? - 60°

Luminaire - LED luminaire with small, mid and high lumen power

Unified Glare Rating - ULOR = 0%

Aplica?ie - Intern / Extern

Lumin? ie?ire (lm) - 13400

Unique digital code (Datamatrix) - Currently not present

Efficiency

(lm/W) - 134

Culoare - Negru

Culoare Temperatur? - 4000 K

Tip surs? de lumin? - LED - Neinlocuibil

Color Rendering Index - CRI 80

Puterea sistemului - 100 W

Standard Deviation Colour Matching - SDCM = 5

LED Lifetime - L80B50 (Tq25°) = 89.000h

Photobiological Risk Class - RG0

Greutate (Kg) - 3.9

Standard - -

Garan?ie - 5 ani

ELETRICAL AND LIGHTING FEATURES - -

Temperatur? de stocare - -40° +80°

Tensiune de alimentare - 220-240 V

Operating temperature - -30° +50°

Frecven?? nominal? (Hz) - 50 / 60

MATERIALS - -

Driver - Included

Body - Aluminiu turnat

Driver failure rate - F05 = 83.500h Tq 25°C

Ecran - Flat silked tempered glass 4mm thick with Gewiss logo

Overvoltage protection - Overvoltage protection 6-4kV

Optic - With high efficiency optic system

Control System - DALI

Gasket - -

INSTALLATION AND MAINTENANCE - -

Locking Hook - -

Mouting and installation - Ceiling - Wall - Floor

External screw - O?el

Tilt - With adjustable bracket assembled

Colour - Powder coating

Wiring - With power cable

STANDARDS AND APPROVALS - -

Prindere - -

Clasificare - -

Optic Maintenance - Not available

Dispozitiv cu temperatur? la suprafa?? redus? - -

LED Maintenance - Not available

Certificare DIN 18032-3 - -

Driver Box - Integrat

IPEA - -

Suprafa?? maxim? expus? la vant - 0,1 m²

Clas? izola?ie - I

- - -

Clas? de protec?ie IP - IP66

- - -

Cod IK - IK08

- - -

Glow Test conductori - 750 °C

- - -

Ware number - 94054010

Pret: 1.272,77 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/lampa-proiector-tip-elia-fl-dali-m2-600-optic-cri-80-4000-k-ip66-class-i-black-215044>