



**GEWISS CORP DE ILUMINAT PLAFONIERA TIP ELIA CL - STAND ALONE  
EMERGENCY - M2 - OPAL DIFFUSED OPTIC - CRI 80 4000 K - IP20/IP54 - CLASS II -  
WHITE**

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Office, Stairs and technical rooms

Optic? - Wide opal

Luminaire - LED luminaire for diffuse light with emergency

Unified Glare Rating - -

Aplica?ie - Intern?

Lumin? ie?ire (lm) - 2550

Unique digital code (Datamatrix) - Currently not present

Efficiency

(lm/W) - 102

Culoare - Alb

Culoare Temperatur? - 4000 K

Tip surs? de lumin? - LED - Neinlocuibil

Color Rendering Index - CRI 80

Puterea sistemului - 25 W

Standard Deviation Colour Matching - SDCM = 3

LED Lifetime - L80B50 (Tq25°) = 50.000h

Photobiological Risk Class - RG0

Greutate (Kg) - 0.8

Standard - -

Garan?ie - 3 ani

ELETRICAL AND LIGHTING FEATURES - -

Temperatur? de stocare - -20° +65°

Tensiune de alimentare - 220-240 V

Operating temperature -  $-0^{\circ}$   $+45^{\circ}$   
Frecven?? nominal? (Hz) - 50 / 60  
MATERIALS - -  
Driver - Included  
Body - Polycarbonate  
Driver failure rate - F025 = 50.000h Tq 25°C  
Ecran - Polycarbonate  
Overvoltage protection - Overvoltage protection 1kV  
Optic - -  
Control System - PORNIT OPRIT  
Gasket - -  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - -  
Mouting and installation - Ceiling - Wall  
External screw - -  
Tilt - -  
Colour - PC coloured  
Wiring - With connection terminal  
STANDARDS AND APPROVALS - -  
Prindere - -  
Clasificare - -  
Optic Maintenance - Not available  
Dispozitiv cu temperatur? la suprafa?? redus? - -  
LED Maintenance - Not available  
Certificare DIN 18032-3 - -  
Driver Box - Integrat  
IPEA - -  
Suprafa?? maxim? expus? la vant - -  
Clas? izola?ie - II  
- - -  
Clas? de protec?ie IP - IP20 - IP54  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - 750 °C  
- - -  
Ware number - 94051098  
Pret: 525,64 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-plafoniera-tip-elia-cl-stand-alone-emergency-m2-opal-diffused-optic-cri-80-4000-k-ip20-ip54-class-ii-white-215053>