



**GEWISS CORP DE ILUMINAT PANEL LED TIP ELIA DL - STAND ALONE - M3 - OPAL  
DIFFUSED OPTIC - CRI 90 3000 K - IP20/IP40 - CLASS II - WHITE**

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Office

Optic? - Wide opal

Luminaire - LED luminaire for diffuse light

Unified Glare Rating - UGR<22

Aplica?ie - Intern?

Lumin? ie?ire (lm) - 3000

Unique digital code (Datamatrix) - Currently not present

Efficiency

(lm/W) - 90

Culoare - Alb

Culoare Temperatur? - 3000 K

Tip surs? de lumin? - LED - Neinlocuibil

Color Rendering Index - CRI 90

Puterea sistemului - 33 W

Standard Deviation Colour Matching - SDCM = 3

LED Lifetime - L80B50 (Tq25°) = 50.000h

Photobiological Risk Class - RG0

Greutate (Kg) - 2.6

Standard - -

Garan?ie - 5 ani

ELETRICAL AND LIGHTING FEATURES - -

Temperatur? de stocare - -20° +65°

Tensiune de alimentare - 220-240 V

Operating temperature - -20° +45°

Frecven?? nominal? (Hz) - 50 / 60

MATERIALS - -

Driver - Included

Body - Aluminiu

Driver failure rate - F025 = 50.000h Tq 25°C

Ecran - PMMA

Overvoltage protection - Overvoltage protection 1kV

Optic - -

Control System - PORNIT OPRIT

Gasket - -

INSTALLATION AND MAINTENANCE - -

Locking Hook - -

Mouting and installation - Montaj incastrat modular

External screw - -

Tilt - With suspension adjustment Kit

Colour - Powder coating

Wiring - With connection terminal on driver

STANDARDS AND APPROVALS - -

Prindere - -

Clasificare - -

Optic Maintenance - Not available

Dispozitiv cu temperatur? la suprafa?? redus? - -

LED Maintenance - Not available

Certificare DIN 18032-3 - -

Driver Box - Independent driver unit

IPEA - -

Suprafa?? maxim? expus? la vant - -

Clas? izola?ie - II

- - -

Clas? de protec?ie IP - IP20 - IP40

- - -

Cod IK - IK03

- - -

Glow Test conductori - -

- - -

Ware number - 94051098

Pret: 447,41 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corp-de-iluminat-panel-led-tip-elia-dl-stand-alone-m3-opal-diffused-optic-cri-90-3000-k-ip20-ip40-class-ii-white-215115>