



**GEWISS PROJECTOR LED TIP SMART [PRO] 2.0 - 1 MODUL - DIMABIL DALI -
ASYMMETRICAL A2 - 5700K (CRI 80) - IP66 - PROTECTION CLASS I**

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Sport, Big Areas

Optic? - A2 - Asymmetrical Medium

Luminaire - LED luminaire with small, mid and high lumen power

Unified Glare Rating - G*3 - ULOR = 0

Aplica?ie - Intern / Extern

Lumin? ie?ire (lm) - 15300

Unique digital code (Datamatrix) - Currently not present

Efficiency

(lm/W) - 93

Culoare - Gri grafit

Culoare Temperatur? - 5700 K

Tip surs? de lumin? - LED - Neinlocuibil

Color Rendering Index - CRI>80

Puterea sistemului - 165 W

Standard Deviation Colour Matching - SDCM = 3

LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=110.000h

Photobiological Risk Class - -

Greutate (Kg) - 5.7

Standard - EN60598-1; EN60598-2-5; EN60598-2-24; IEC 62778; IEC62471; EN13201

Garan?ie - 5 ani

ELETRICAL AND LIGHTING FEATURES - -

Temperatur? de stocare - -

Tensiune de alimentare - 220 - 240 V

Operating temperature - -30 +50 °C

Frecven?? nominal? (Hz) - 50 / 60

MATERIALS - -

Driver - Included

Body - Aluminiu turnat

Driver failure rate - F10 = 100.000h Tq25°C

Ecran - Flat tempered glass 4mm

Overvoltage protection - DM 6 kV / CM 10 kV

Optic - Polished anodised aluminum reflector with 99.99% pure aluminum

Control System - DALI

Gasket - Anti-aging silicone

INSTALLATION AND MAINTENANCE - -

Locking Hook - Hexagonal metric screws

Mouting and installation - High-mast lighting - Wall mounting - Ground mouting

External screw - Stainless steel

Tilt - Rotation on bracket with integrated goniometer

Colour - Polyester powder coated

Wiring - Watertight connector

STANDARDS AND APPROVALS - -

Prindere - Consol?

Clasificare - -

Optic Maintenance - Not available

Dispozitiv cu temperatur? la suprafa?? redus? - Da

LED Maintenance - Not available

Certificare DIN 18032-3 - Da

Driver Box - Integrat

IPEA - -

Suprafa?? maxim? expus? la vant - 0,085 m2

Clas? izola?ie - I

- - -

Clas? de protec?ie IP - IP66

- - -

Cod IK - IK08

- - -

Glow Test conductori - -

- - -

Ware number - 94054010

Pret: 2.211,06 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/proiector-led-tip-smart-pro-2-0-1-modul-dimabil-dali-asymmetrical-a2-5700k-cri-80-ip66-protection-class-i-215419>