



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] - OPAL SHIELD -**  
**CONECTOR CONEXIUNE RAPIDA- STAND ALONE - 800MM - 3000 K (CRI 80) -**  
**220/240V 50/60HZ - IP66/IP69 - CLASS II**

Aplica?ie - Intern?  
Seria - SMART [3]  
Tip - Autonom - Conexiune cablaj rapid  
Clas? de protec?ie IP - IP66/IP69  
Cod IK - IK08  
Clas? izola?ie - II  
Glow Test conductori - 850 °C  
Lungimea - 800 mm  
Dispozitiv cu temperatur? la suprafa?? redus? - Conform  
Ecran - Opal  
Temperatur? de operare - -30 +50 °C  
Greutate (Kg) - 1.5  
Tensiune - 220/240 V - 50/60 Hz - Autonom  
Lampa tip - LED  
Tip driver - LED driver de curent constant  
Puterea sistemului - 15 W  
Tip surs? de lumin? - LED - Neinlocuibil  
Temperatur? de culoare - 3000 K (CRI>80)  
Clas? de eficien?? a LED-urilor integrate - A ÷ A++  
Flux nominal (lm) - 2000  
Lumin? ie?ire (lm) - 1400  
LED Life Time (L80B50) - 100000 h  
LED Life Time (L90B50) - 50000 h  
Durat? utilizare LED L80B20 - 85000 h  
Failure rate apparecchio (35.000h, Tq=35° C) - <2,5%

Failure rate apparecchio (50.000h, Tq=25° C) - <2,5%

Garan?ie - 5 ani

Overvoltage resistance - Common mode: 2KV; Differential mode: 1KV

Electrocod - 2434

Ware number - 94051040

Pret: 394,44 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-opal-shield-conector-conexiune-rapida-stand-alone-800mm-3000-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216171>