



GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] - DIFUZOR OPAL -
CONECTOR CONEXIUNE RAPIDA - STAND ALONE - 1200MM - 5700 K (CRI 80) -
220/240V 50/60HZ - IP66/IP69 - CLASS II

Aplica?ie - Intern?

Seria - SMART [3]

Tip - Autonom

Clas? de protec?ie IP - IP66/IP69

Cod IK - IK08

Clas? izola?ie - II

Glow Test conductori - 850 °C

Lungimea - 1200 mm

Dispozitiv cu temperatur? la suprafa?? redus? - Conform

Ecran - Opal cu cablaj de trecere

Temperatur? de operare - -30 +50 °C

Greutate (Kg) - 2

Tensiune - 220/240 V - 50/60 Hz - Autonom

Lampa tip - LED

Tip driver - LED driver de curent constant

Puterea sistemului - 20 W

Tip surs? de lumin? - LED - Neinlocuibil

Temperatur? de culoare - 5700 K (CRI>80)

Clas? de eficien?? a LED-urilor integrate - A ÷ A++

Flux nominal (lm) - 2900

Lumin? ie?ire (lm) - 2300

LED Life Time (L80B50) - 100000 h

LED Life Time (L90B50) - 50000 h

Durat? utilizare LED L80B20 - 85000 h

Failure rate apparecchio (35.000h, Tq=35° C) - <2,5%

Failure rate apparecchio (50.000h, Tq=25° C) - <2,5%

Garan?ie - 5 ani

Overvoltage resistance - Common mode: 2KV; Differential mode: 1KV

Electrocod - 2434

Ware number - 94051040

Pret: 477,80 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-difuzor-opal-conector-conexiune-rapida-stand-alone-1200mm-5700-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216240>