



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] - DISPERSOR
TRANSPARENT - DALI - 1600MM - 5700 K (CRI 80) - 220/240V 50/60HZ - IP66/IP69 -
CLASS II**

Aplica?ie - Intern?
Seria - SMART [3]
Tip - DALI
Clas? de protec?ie IP - IP66/IP69
Cod IK - IK08
Clas? izola?ie - II
Glow Test conductori - 850 °C
Lungimea - 1600 mm
Dispozitiv cu temperatur? la suprafa?? redus? - Conform
Ecran - Transparent
Temperatur? de operare - -30 +50 °C
Greutate (Kg) - 2.5
Tensiune - 220/240 V - 50/60 Hz - Dali
Lampa tip - LED
Tip driver - LED driver de curent constant
Puterea sistemului - 26 W
Tip surs? de lumin? - LED - Neinlocuibil
Temperatur? de culoare - 5700 K (CRI>80)
Clas? de eficien?? a LED-urilor integrate - A ÷ A++
Flux nominal (lm) - 3700
Lumin? ie?ire (lm) - 3400
LED Life Time (L80B50) - 100000 h
LED Life Time (L90B50) - 50000 h
Durat? utilizare LED L80B20 - 85000 h
Failure rate apparecchio (35.000h, Tq=35° C) - <2,5%

Failure rate apparecchio (50.000h, Tq=25° C) - <2,5%

Garan?ie - 5 ani

Overvoltage resistance - Common mode: 2KV; Differential mode: 1KV

Electrocod - 2434

Ware number - 94051040

Pret: 556,03 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-dispersor-transparent-dali-1600mm-5700-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216273>