



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] - DISPERSOR  
TRANSPARENT - CONECTOR CONEXIUNE RAPIDA - DALI - 1600MM - 3000 K (CRI 80)  
- 220/240V 50/60HZ - IP66/IP69 - CLASS II**

Aplica?ie - Intern?

Seria - SMART [3]

Tip - DALI

Clas? de protec?ie IP - IP66/IP69

Cod IK - IK08

Clas? izola?ie - II

Glow Test conductori - 850 °C

Lungimea - 1600 mm

Dispozitiv cu temperatur? la suprafa?? redus? - Conform

Ecran - Transparent

Temperatur? de operare - -30 +50 °C

Greutate (Kg) - 2.5

Tensiune - 220/240 V - 50/60 Hz - Dali

Lampa tip - LED

Tip driver - LED driver de curent constant

Puterea sistemului - 26 W

Tip surs? de lumin? - LED - Neinlocuibil

Temperatur? de culoare - 3000 K (CRI>80)

Clas? de eficien?? a LED-urilor integrate - A ÷ A++

Flux nominal (lm) - 3500

Lumin? ie?ire (lm) - 3200

LED Life Time (L80B50) - 100000 h

LED Life Time (L90B50) - 50000 h

Durat? utilizare LED L80B20 - 85000 h

Failure rate apparecchio (35.000h, Tq=35° C) - <2,5%

Failure rate apparecchio (50.000h, Tq=25° C) - <2,5%

Garan?ie - 5 ani

Overvoltage resistance - Common mode: 2KV; Differential mode: 1KV

Electrocod - 2434

Ware number - 94051040

Pret: 638,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-dispersor-transparent-conector-conexiune-rapida-dali-1600mm-3000-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216277>