



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] C - OPAL SHIELD -  
STAND ALONE - 800MM - 4000 K (CRI 80) - 220/240V 50/60HZ - IP66 - CLASS II**

Aplica?ie - Intern?

Seria - SMART [3] COMPACT

Tip - Autonom

Clas? de protec?ie IP - IP66

Cod IK - IK08

Clas? izola?ie - II

Glow Test conductori - 850 °C

Lungimea - 800 mm

Dispozitiv cu temperatur? la suprafa?? redus? - Conform

Ecran - Opal

Temperatur? de operare - -20 +35 °C

Greutate (Kg) - 1.5

Tensiune - 220/240 V - 50/60 Hz - Autonom

Lampa tip - LED

Tip driver - LED driver de curent constant

Puterea sistemului - 35 W

Tip surs? de lumin? - LED - Neinlocuibil

Temperatur? de culoare - 4000 K (CRI>80)

Clas? de eficien?? a LED-urilor integrate - A ÷ A++

Flux nominal (lm) - 4300

Lumin? ie?ire (lm) - 3700

LED Life Time (L80B50) - 90000 h

Durat? utilizare LED L80B20 - 70000 h

Failure rate apparecchio (35.000h, Tq=35° C) - <10%

Failure rate apparecchio (50.000h, Tq=25° C) - <10%

Garan?ie - 3 ani

Overvoltage resistance - Common mode: 2KV; Differential mode: 1KV

Electrocod - 2434

Ware number - 94051040

Pret: 473,50 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-c-opal-shield-stand-alone-800mm-4000-k-cri-80-220-240v-50-60hz-ip66-class-ii-216363>