



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] C - DISPERSOR
TRANSPARENT - STAND ALONE - 1200MM - 4000 K (CRI 80) - 220/240V 50/60HZ - IP66 -
CLASS II**

Aplica?ie - Intern?
Seria - SMART [3] COMPACT
Tip - Autonom
Clas? de protec?ie IP - IP66
Cod IK - IK08
Clas? izola?ie - II
Glow Test conductori - 850 °C
Lungimea - 1200 mm
Dispozitiv cu temperatur? la suprafa?? redus? - Conform
Ecran - Transparent
Temperatur? de operare - -20 +35 °C
Greutate (Kg) - 2
Tensiune - 220/240 V - 50/60 Hz - Autonom
Lampa tip - LED
Tip driver - LED driver de curent constant
Puterea sistemului - 56 W
Tip surs? de lumin? - LED - Neinlocuibil
Temperatur? de culoare - 4000 K (CRI>80)
Clas? de eficien?? a LED-urilor integrate - A ÷ A++
Flux nominal (lm) - 6900
Lumin? ie?ire (lm) - 6700
LED Life Time (L80B50) - 90000 h
Durat? utilizare LED L80B20 - 70000 h
Failure rate apparecchio (35.000h, Tq=35° C) - <10%
Failure rate apparecchio (50.000h, Tq=25° C) - <10%

Garan?ie - 3 ani

Overvoltage resistance - Common mode: 2KV; Differential mode: 1KV

Electrocod - 2434

Ware number - 94051040

Pret: 503,90 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-c-dispersor-transparent-stand-alone-1200mm-4000-k-cri-80-220-240v-50-60hz-ip66-class-ii-216403>