



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] - TRANSPARENT  
DIFFUSER - CONECTOR CONEXIUNE RAPIDA - STAND ALONE - 1600MM - 5700 K  
(CRI 80) - 220/240V 50/60HZ - IP66/IP69 - CLASS II**

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Lighting of warehouses, indoor parking and industrial production rooms

Optic? - Microprismatic transparent

Luminaire - LED fixture for general lighting

Unified Glare Rating - UGR ? 25 (4H/4H)

Aplica?ie - Intern?

Lumin? ie?ire (lm) - 6700

Unique digital code (Datamatrix) - Datamatrix

Efficiency

(lm/W) - 134

Culoare - Grey (RAL 7035)

Culoare Temperatur? - 5700 K

Tip surs? de lumin? - LED - Neinlocuibil

Color Rendering Index - CRI>80

Puterea sistemului - 50 W

Standard Deviation Colour Matching - SDCM = 3

LED Lifetime - L90B10(Tq25°C)=45.000h; L80B10(Tq25°C)=92.000h

Photobiological Risk Class - RG0

Greutate (Kg) - 2.5

Standard - EN60598-1; IEC 62778; IEC62471

Garan?ie - 5 ani

ELETRICAL AND LIGHTING FEATURES - -

Temperatur? de stocare - -25 +80 °C

Tensiune de alimentare - 220 - 240 V

Operating temperature - -25 +50 °C

Frecven?? nominal? (Hz) - 50/60 Hz

MATERIALS - -

Driver - Included

Body - Polycarbonate

Driver failure rate - F10 = 100.000h Tq25°C

Ecran - UV stabilised polycarbonate

Overvoltage protection - DM 1KV / CM 2KV

Optic - Integrated in the screen

Control System - Through wiring - On/Off

Gasket - CNC deposited sealant

INSTALLATION AND MAINTENANCE - -

Locking Hook - -

Mouting and installation - Ceiling - Wallmounting - Suspension

External screw - -

Tilt - With fixing bracket

Colour - RAL7035 colored PC paste

Wiring - With GW connect watertight connector

STANDARDS AND APPROVALS - -

Prindere - Stainless steel support

Clasificare - -

Optic Maintenance - Not available

Dispozitiv cu temperatur? la suprafa?? redus? - Da

LED Maintenance - Not available

Certificare DIN 18032-3 - Not available

Driver Box - Integrat

IPEA - -

Suprafa?? maxim? expus? la vant - -

Clas? izola?ie - II

- - -

Clas? de protec?ie IP - IP66/IP69

- - -

Cod IK - IK08

- - -

Glow Test conductori - 850 °C

- - -

Ware number - 94051040

Pret: 564,69 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-transparent-diffuser-conector-conexiune-rapida-stand-alone-1600mm-5700-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216409>