



## **LEGRAND 180° SENZOR DE MISCARE MOSAIC - 15 M<sup>2</sup> - DUAL-TECH - VACANCY MODULE CU NEUTRAL - ALB**

### Caracteristici tehnice

3-wire presence sensor, with neutral

Infrared and ultrasonic double technology

Allows a precise presence detection. Checks the light level continuously and not only at the time of detection

Propose a special mode: manual switching on with integrated pushbutton, automatic switching off

Accepted Putere by lamp type:

LEDs: 0 to 250 W

Compact fluorescent: 0 to 250 W

LEDs, CFLs, Halogen, fluo tubes with ferromagnetic or electronic transformer: 0 to 1000 VA

Halogen 230 V, incandescent: 0 to 2000 W

Up to 10 sensors can be connected in parallel

Additional remote manual control possible with push button

Time delay setting from 5 s to 30 min

Light level threshold setting from 5 lux to 1275 lux

Standby Consum : 0.4 W

Mosaic

With neutral

### Caracteristici generale

Mosaic™ Programme mechanisms - motion and presence sensors

All sensors are compatible with any lamp - Detection field: 120°

Detection range: 8 m

Recommended installation height: 1.20 m

Integrated self-protection against overloads and short-circuits.

2 module

Pret: 721,27 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1800-senzor-de-miscare-mosaic-15-m2-dual-tech-vacancy-module-cu-neutral-alb-221720>