



## **LEGRAND SET PRIZE 19" PDU LCS<sup>3</sup> - 1 U - 6 X C19 - IEC 60320 STANDARD**

Caracteristici tehnice

19" - PDU Basic

IEC 60320 standard

Connection on terminal block (except Cat.No 6 468 15)

6 C19 outlets with cord locking system

Caracteristici generale

Legrand cabling system LCS<sup>3</sup> energy Distribution - horizontal (1U/2U) Basic Putere Distribution Units (PDU)

To provide ~ electric Putere for IT equipment in 19" enclosures

230 V - 50/60 Hz Tensiune de alimentare

1U aluminium profile

End cap with metallic brackets and cable holder shape

Quick fixing (no screws) on 19" fixing centers. Can also be installed vertically by reverting the brackets (no screws)

2P+E outlets:

C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection.

Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19)

French, German and British standard outlets are equipped with safety shutters

French and German standard outlets are inclined at 55°

Black module (outlets and functions)

Pret: 255,53 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/set-prize-19-pdu-lcs3-1-u-6-x-c19-iec-60320-standard-221764>