



### **LEGRAND ADD-ON MODULE DX<sup>3</sup> - 4P- 400 V~ - 125 A- 30/3000 MA- HPI TYPE / INTEGRATED MEASUREMENT**

#### Caracteristici tehnice

4-pole 400 V~ - Measurement

LCD display

For displaying current per phase, Tensiune, frequency, active and reactive Putere, Putere factor, active and reactive energy Consum and harmonics

F type (old Hpi type) with integrated measurement unit

Sensitivity : 30 to 3000 mA

Nominal rating In : 125 A

Numar de module : 7.5

#### Caracteristici generale

Add-on module DX<sup>3</sup> - for 1.5 module/pole DX<sup>3</sup> MCBs

Conform to IEC 61009-1, IEC 62423 (F type)

Tensiune independent tripping except Cat.Nos 4 106 57/58/59

AC type : detect AC components faults

F type (High immunity) : detect faults with AC and DC components, increased immunity to false tripping

Detection of high frequency fault currents

For mounting on the Dreapta-hand side of 1.5 module per pole DX<sup>3</sup> MCBs

Pret: 4.802,70 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/add-on-module-dx3-4p-400-v-125-a-30-3000-ma-hpi-type-integrated-measurement-222477>