



LEGRAND ADD-ON DESCARCATOR SPD - T2 - IMAX 20 KA/POLE - 1P+N LEFT

Caracteristici tehnice

T2 add-on SPDs

SPDs with plug-in module and status indicators:

Green: SPD operational

Orange: plug-in module to be replaced

To be equipped with DX³ MCBs (1 module/pole)

Earthing systems: TT, TNS

T2 - I_{max} 20 kA/pole

SPDs recommended for small installations

Up: 1.2 kV - I_n: 5 kA/pole - U_c: 320 V~

Recommended MCB: DX³ 20A - C curve

1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1

Numar de poli : 1P+N

Pozitie NUL : Stanga

Remote status monitoring (FS contact) : Yes

Numar de module : 4

Caracteristici generale

Class II (T2) low Tensiune SPDs

Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz). SPDs compliant with EN/IEC 61643-11 standards

Recommended for distribution boards

Pret: 395,81 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/add-on-descarcator-spd-t2-imax-20-ka-pole-1p-n-left-222496>