



LEGRAND AUTOMATIC SWITCH PLEXO CU NEUTRAL - 3-WIRE - IP55 IK10

Caracteristici tehnice

Automatic switches - IK 10 - IP 55

Infrared detection

Detection distance: 8 m

Detection angle: 120°

Light level threshold: 5 to 1275 lux

Adjustable time delay: 10 s to 10 min

Should preferably be installed in box depth 50 mm

With neutral, 3-wire

For controlling lamps :

LEDs: 0 to 250 W

compact fluorescent: 0 to 250 W

LEDs, CFLs with ferromagnetic or electronic ballast: 0 to 250 V~

halogen with ferromagnetic or electronic ballast: 0 to 500 V~

fluorescent tube with ferromagnetic or electronic ballast: 0 to 5 x (2 x 36 W)

230 V halogen, incandescent: 0 to 1000 W

Option of connecting several automatic switches in parallel

Consum on standby: 0.035 W

Caracteristici generale

Soliroc™ - control mechanisms IK 10

Suitable for public buildings, unsupervised passageways, car parks, communal areas in buildings

High resistance to IK 10 impacts and humidity

4 fixing points by plugging the plate directly on the wall and 4 blanking plates to be force-mounted on the plate (can only be removed by drilling)

Mechanisms supplied with cover plates, to be equipped with support frames and plates

Pret: 508,08 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/automatic-switch-plexo-cu-neutral-3-wire-ip55-ik10-222791>