



**LEGRAND AUTOMATIC SWITCH PLE XO CUOUT NEUTRAL - 2-WIRE - IP55 IK07 -  
230 V~ - 50 HZ - GRI/ALB**

Caracteristici tehnice

Automatic switches 230 V~ - 50 Hz

IP 55 - IK 07

Infrared detection

Detection distance: 8 m

Detection angle 120°

Adjustable time delay: 10 s to 10 min

Light level threshold: 5 to 1275 lux

Should preferably be installed in box depth 50 mm

Without neutral, 2-wire

For installation in place of a 1-gang switch, with no additional wiring

For controlling lamps:

LEDs: 3 to 100 W

compact fluorescent: 3 to 100 W

LEDs, CFLs, halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 to 250 VA

230 V halogen, incandescent: 3 to 250 W

Option of connecting up to 3 automatic switches

For LEDs and compact fluorescent lamps, if several automatic switches are installed on the same circuit, the minimum load increases

Consum on standby: 0.02 W

Grey/White

Caracteristici generale

Plexo™ mechanisms - switches, push-buttons and automatic switches IP 55

Mechanisms supplied with cover plate

Installation with surface-mounting boxes or Montaj incastrat support frames

Automatic terminals

Pret: 555,08 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/automatic-switch-plexo-cuout-neutral-2-wire-ip55-ik07-230-v-50-hz-gri-alb-222792>