



LEGRAND AUTOTEST/ADRESSABLE LUMINAIRES U34 LED - 1H DURATION CU OPAL DIFFUSER - 250 LM

Caracteristici tehnice

Autotest and addressable luminaires - Maintained/Non-maintained (M/NM)

Autotest/addressable luminaires incorporate an automatic self-testing system

Tests result is visible on 2 signalling LEDs (green-OK and yellow-defective)

Addressable function is activated by setting an ID on each luminaire with infrared configuration tool (Cat.No. 0 626 10) and wiring a complementary BUS line

Operating state of all addressable luminaires can be centralized by the control interface (Cat. No. 0 626 00) and monitored on a local touch screen controller (Cat.No 0 626 01), or with the building's plan on Legrand Vision System (LVS2) PC software Cat.No 0 626 02

1 h duration with transparent diffuser

250 lm - 1h (LEDs)

Caracteristici generale

U34LED environment friendly - indoor self-contained emergency lighting luminaires LED

LED Maintained/Non-maintained units

High Putere LEDs with specially designed lenses optimizing the lighting distribution

IP 42 - IK 07 - Class II

Tensiune de alimentare: 230 V \pm 10% - 50/60 Hz

Very low Consum switching Tensiune de alimentare - Fully recyclable after removing

Environment friendly Ni-MH batteries

Removable plug-in plate to ease installation and maintenance

Automatic terminals with high capacity: 2 x 2.5 mm²

Charge monitor with a green LED

Can be equipped with metallic protection grids Cat.Nos 0 626 92/93

Pret: 959,85 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/autotest-adressable-luminaires-u34-led-1h-duration-cu-opal->

